



For use with Titon HRV Q Plus Range

auramode® is a simple yet powerful LCD display for programming, commissioning and occupancy control for Titon's range of Mechanical Ventilation Heat Recovery (MVHR) units.

The auramode® allows straightforward operation of ventilation speeds at a click of a button. Offering a display that is back lit with adjustable light and contrast settings.

- auramode® provides the following functions:
- Digital 4 speed switch (speeds 1, 2, 3 or 4)
- Auto timed speed mode
- 7-day, 8 settings per day programmable speeds
- Filter change indicator with adjustable (1-24 months independent filter check and filter change intervals)
- Internal MVHR humidity set point adjustment
- Boost inhibit functions linked to timed speeds (avoiding night time boosting via either switch inputs or humidity)

auramode® is a multi-language controller where the user can select from the following languages:

English
Dutch
French
German
Italian
Spanish
Polish
Lithuanian
Russian
Ukrainian
Slovenian
Hungarian

Features & Benefits

- User friendly interface
- Fan speed commissioning
- Multiple languages available
- Digital 3 or 4 speed switch (user selectable)
- 7 day, 8 programmable fan speed settings
- Boost inhibit
- Compact design
- Filter change indication
- Internal MVHR humidity sensor set point
- Compatible with TP***B MVHR models
- Kitchen boost overrun timer adjustment
- Wet room boost overrun timer adjustment
- Volt free and mains voltage MVHR Switch configuration setup
- Humidity set point adjustment
- High flow boost setting (speed 4)
- Summerboost boost on/off selection
- Single button operation for everyday basic functions
- Low voltage, hard wired status programmer

Description

Titon's auramode® HRV is for commissioning and monitoring a Titon TP***B HRV Q Plus unit.

Product Code

auramode® - TP524

Specification

Dimensions: 86mm wide x 86mm high x 16mm deep Supplied with 14 metre connection cable (plug connection to auramode, 4 wire to MVHR)

Weight: 185g

Finish: High gloss finish

Materials: ABS

Guarantee period: 1 year

Electrical: 12V DC