

# Solis-1P3.6K-4G

## Solis 4G Single Phase Inverters



### Features:

- Solis 1P 4G Single Phase Range
- High frequency switching technology - Smaller, smarter
- Dual MPPT design with precise MPPT algorithm
- Intergrated Export Power Manager(EPM)
- Over 97.8% Max. effciency
- RS485, WiFi/LAN/GPRS (optional) interface
- WiFi monitoring available-Android and Apple App store available

### Model:

Solis-1P3.6K-4G

### Datasheet

Model Name		Solis-1P3.6K-4G
Input DC		
Max. DC input power(kW)		4.2
Max. DC input voltage(V)		600
Start-up voltage(V)		120
MPPT voltage range(V)		90-520
Max. input current(A/B)		11A+11A
Max. Short Circuit current for each MPPT		17.2A+17.2A
MPPT number/Max input strings number		2/A;1; B:1
Output AC		
Rated output power(kW)		3.6
Max. apparent output power(kVA)		4
Max. output power(kW)		4
Rated grid voltage(V)		220/230
Rated grid frequency(Hz)		50/60
Grid frequency range(Hz)		47-52 or 57-62
Operation phase		Single Phase
Rated grid output current(A)		16/15.7
Max. output current(A)		16
Power Factor (at rated output power)		0.8leading ... 0.8lagging
THDi (at rated output power)		<3%
DC injection current		<0.5%In
Efficiency		
Max. efficiency		97.8%
EU efficiency		97.1%
MPPT efficiency		>99.5%
Protection		
DC reverse-polarity protection		Yes
Short circuit protection		Yes
Output over current protection		Yes
Output over voltage protection		Yes
Insulation resistance monitoring		Yes
Residual current detection		Yes
Surge protection		Yes
Grid monitoring		Yes
Islanding protection		Yes
Temperature protection		Yes
Integrated DC switch		Optional
General Data		
Dimensions(mm)		310W*543H*160D
Weight (kg)		11.5
Topology		Transformer less
Self consumption (night)		<1W (Night)
Operating ambient temperature range		-25~60°C
Relative humidity		0~100%
Ingress protection		IP65
Noise emission(typical)		<20dBA
Cooling concept		Natural convection
Max. operation altitude		4000m
Designed lifetime		>20 years
Grid connection standard		EN50438, AS4777.2:2015, VDE0126-1-1, IEC61727, VDE N4105, G98, G99
Safty/EMC standard		IEC62109-1/-2, NB/T 32004, EN61000-6-1, EN61000-6-3
Features		
DC connection		MC4
AC connection		IP67 rated plug
Display		LCD, 2x20 Z.
Communication connections		4 pins RS485 connector
Monitoring		WiFi or GPRS
Warranty		5/ 10/ 15/ 20 Years