



SOLARIF

RISK MANAGEMENT

Certificate number: **PV 20180525000**
Certificate holder: **Ulica Solar Science & Technology Co., Ltd.**

Valid from: **26.04.2018**
Expires on: **26.04.2019**

Solarif Risk Management B.V. declares, after a thorough risk assessment of amongst others the production lines, financial strength, environmental and labor conditions, that the modules mentioned below from the **Ulica Solar Science & Technology Co., Ltd.** factory located at No. 181, Shanshan Road, Wangchun Industrial Area, Yinzhou District, 315177 - Ningbo, Zhejiang, China, are approved.

The certificate is valid from **26.04.2018** until **26.04.2019** and as long as the company is not insolvent.

This certificate enables clients of **Ulica Solar Science & Technology Co., Ltd.** to purchase Solarif's unique inherent defect coverage in addition to Solarif's Operational all risk insurance, supporting and backing-up the manufacturer's warranty in case of inherent defect.

This insurance is exclusively available through Solarif Insurance.

For more information or a quotation, please contact us at +31 (0) 26 711 5050, by email midoffice@solarif.com or visit our website www.solarif.com.

Date: <**25.05.2018**>

Harry Wolkenfelt / CEO
Solarif Risk Management BV



CERTIFICATE

Certificate number: **PV 20180525000**
 Certificate holder: **Ulica Solar Science & Technology Co., Ltd.**

Valid from: **26.04.2018**
 Expires on: **26.04.2019**

APPROVED MONO-CRYSTALLINE MODULES				
<i>Model</i>	<i>Max. Power (Wp)</i>	<i>Tolerance</i>	<i>Euro. Efficiency</i>	<i>Number and size of cell</i>
UL-xxM-24	95	±3	1000	24/ 156mm x 156mm
UL-xxxM-24	100-120	±3	1000	24/ 156mm x 156mm
UL-xxxM-28	105-140	±3	1000	28/ 156mm x 156mm
UL-xxxM-32	120-155	±3	1000	32/ 156mm x 156mm
UL-xxxM-36	135-175	±3	1000	36/ 156mm x 156mm
UL-xxxM-48	170-240	±3	1000	48/ 156mm x 156mm
UL-xxxM-54	190-270	±3	1000	54/ 156mm x 156mm
UL-xxxM-60	210-300	±3	1000	60/ 156mm x 156mm
UL-xxxM-72	250-360	±3	1000	72/ 156mm x 156mm
UL-xxD-16	40-50	±3	1000	16/ 125mm x 125mm
UL-xxD-20	50-60	±3	1000	20/ 125mm x 125mm
UL-xxD-24	60-75	±3	1000	24/ 125mm x 125mm
UL-xxD-28	65-90	±3	1000	28/ 125mm x 125mm
UL-xxD-32	75-95	±3	1000	32/ 125mm x 125mm
UL-xxxD-32	100	±3	1000	32/ 125mm x 125mm
UL-xxD-36	80-95	±3	1000	36/ 125mm x 125mm
UL-xxxD-36	100-115	±3	1000	36/ 125mm x 125mm
UL-xxD-40	90-95	±3	1000	40/ 125mm x 125mm
UL-xxxD-40	100-125	±3	1000	40/ 125mm x 125mm
UL-xxxD-72	155-230	±3	1000	72/ 125mm x 125mm
UL-xxxD-84	165-270	±3	1000	84/ 125mm x 125mm
UL-xxxD-96	235-305	±3	1000	96/ 125mm x 125mm





SOLARIF

RISK MANAGEMENT

APPROVED POLY-CRYSTALLINE MODULES				
<i>Model</i>	<i>Max. Power (Wp)</i>	<i>Tolerance</i>	<i>Euro. Efficiency</i>	<i>Number and size of cell</i>
UL-xxxP-24	100-115	±3	1000	24/ 156mm x 156mm
UL-xxxP-28	105-135	±3	1000	28/ 156mm x 156mm
UL-xxxP-32	120-155	±3	1000	32/ 156mm x 156mm
UL-xxxP-36	140-175	±3	1000	36/ 156mm x 156mm
UL-xxxP-48	160-235	±3	1000	48/ 156mm x 156mm
UL-xxxP-54	180-265	±3	1000	54/ 156mm x 156mm
UL-xxxP-60	200-295	±3	1000	60/ 156mm x 156mm
UL-xxxP-72	240-355	±3	1000	72/ 156mm x 156mm

